

# SAVEMA 20 i&c&tr SERIES THERMAL TRANSFER OVERPRINTERS

## 53\*200 I



### Common Specifications for All Printers

**Software:** SAYASIS Template Design (Date and Time, Custom Formatted Date and Time, Text, Text Block, Merge Fields, Database Support, Counter, Logo, 1D / 2D Barcodes, GS-1 Barcodes, Table Creation Support and User-Friendly Interface)

Windows Driver Support, Nicelabel Software support, Code soft Software Support, Emulator Support, Printer Management with SPPL (Savema Protocol) Commands, Printer Control with Remote Control)

**Barcodes:** 1D Barcodes (EAN-13, EAN-8, CODE 128, CODE 39, CODABAR, ITF 2of5, ITF 14, UPC-A, UPC-E ...), 2D Barcodes (Datamatrix, QR Code, PDF417, Aztec code...), GS-1 Barcodes (GS1-128, GS1-Datamatrix, GS1-Databar Barcodes)

**Resolution:** 300dpi (12 dots/mm) horizontally and vertically

**Operating Temperature:** 1 °C - 55 °C (34°F-131°F)

**Memory:** Max. 5000 Template Storage Capacity, 1GB Internal Memory, Up to 16GB SD Memory Card Support, Up to 32GB USB Memory Support

Specifications	53* 200 I (Intermittent)
Print Area	53 mm x 200 mm
Print Speed	50 - 400 mm/sec
Production	Max. 235 prints/min
Ribbon Widths & Length	35mm, 55 mm & 600 meters loaded ribbon
Power Supply	100-240V 50-60 Hz
Air Supply (Bar)	Min. 1 bar - Max. 4 bar
Input/Outputs	Print Signal/Fault Signal, Busy Signal
Output Messages	Update Error, Contact Error, Ribbon Break / Not Found Error, Remaining Ribbon Quantity, Number of Printed Templates, Number of Prints per Minute
Connection Types	Relay(NPN, PNP) - Photocell(NPN, PNP)
Communications	RS-232, Ethernet, USB
Ribbon Save Modes	Vertical & Horizontal Ribbon Save Modes
Advanced Control	7" Touch Screen Control, Template Changing while Running, Print Position Adjustment, Contrast, Print Delay, Template-Specific Adjustment, Internal Contact Signal, Multi-printContact Signal, Template Shifting, Template Rotation
Operator Interface	7" 800x480 Pixels Resolution, Full-color display, Password protection on menus, Multi-language(20) support
Weight (Printer)	12,5 Kg
Dimensions	180mm H x 248mm W x 345 mm D

