

SAVEMA 20 f SERIES FEEDER & CONVEYOR BELT

SVM 100-A1 FRICTION FEEDER



SVM 100-A2 VACUUM FEEDER

SVM 100-B1 CONVEYOR BELT


SVM 100-B2 CONTINUOUS CONVEYOR BELT



**SVM 100 - A1
FRICTION FEEDER**



**SVM 100 - A2
VACUUM FEEDER**



Friction Feeder Specifications

Min. Width of Product	50mm (W) x 80mm (L)
Max. Width of Product	300mm (W) x 400mm (L)
Min-Max Product Thickness	0,1 - 4 mm (depend on product type)
Belt Speed	600 mm/sec.
Power	100-120V 50-60 Hz 200-240V 50-60 Hz
Weight	20 Kg

Vacuum Feeder Specifications

Min. Width of Product	100mm (W) x 100mm (L)
Max. Width of Product	300mm (W) x 320mm (L)
Power	100-120V 50-60 Hz 200-240V 50-60 Hz
Weight	14 Kg

**SVM 100 - B1
CONVEYOR BELT**



**SVM 100 - B2
CONTINUOUS CONVEYOR BELT**



Specifications	Conveyor Belt (Intermittent)	Continuous Conveyor Belt
Min. Width of Product	50mm (W) x 80mm (L)	50mm (W) x 80mm (L)
Max. Width of Product	300mm (W) x 400mm (L)	300mm (W) x 400mm (L)
Belt Speed	50-500 mm/sec.	50-500 mm/sec.
Power	100-120V 50-60 Hz & 200-240V 50-60 Hz	100-120V 50-60 Hz & 200-240V 50-60 Hz
Weight	55 Kg	55 Kg
Operation Mode	Intermittent/Continuous	Intermittent/Continuous